



Showtec Performer 2500 Fresnel Q6

250W RGBALC LED Fresnel
 Suitable for theatrical application
 CCT colour temperature range of 1800K – 8000K
 Wide manually adjustable zoom range
 16 Preset Colours

SOURCE

Light Source Type	LED	Beam Angle Circular (min)	10 deg
Light Source Quantity	1	Beam Angle Circular (max)	60 deg
Light Source Power	250W	Field Angle Circular (min)	18 deg
Led Colour Type	RGBALC	Field Angle Circular (max)	88 deg
Refresh Rate (min)	600 Hz	Zoom Type	Manual
Refresh Rate (max)	25 kHz		
Lux @ 2m	26812 lx		
Lumen Total	7661 lm		

OPTICAL

CONTROL & PROGRAMMING

CRI	90	Control Mode	DMX, Stand Alone
CCT Minimum	1800K	DMX Channels	3,6,7,9,10,13,20
CCT Maximum	8000K	Protocols	DMX, RDM
		Display	LCD

DYNAMIC EFFECTS

Dimmer	0-100%		
Strobe	0-25Hz		

MECHANICAL SPECS

		Length	470mm
		Width	380mm
		Height	450mm

ELECTRIC SPECIFICATIONS & CONNECTIONS

Power Supply	100-240 VAC 50-60Hz	Weight	5.5kgs
Power Consumption	250W	IP Rating	IP20 (indoor only)
Power Connector in	PowerCON True 1 in (m)	Housing	Aluminium Die Cast
Power Connector out	PowerCON True 1 out (f)	Colour	Black
DMX Connector	XRL 5P IN/OUT		

TERMAL SPECIFICATIONS

		Max Ambient Temp	70 deg C
Cooling	Axial Fan	Max Surface Temp	40 dec C
		Min Operating Temp	0 deg C

PRODUCT PROPERTIES

CERTIFICATIONS

Reference Standards	CE	Included Cables	PowerCON True1
---------------------	----	-----------------	----------------

INCLUDED ITEMS



Clearlight Shows Pty Ltd