34035

Showtec Act Profile 150W RGBAL Compact 150 W RGBAL Theatre LED Profile

Compact 150 W RGBAL Theatre LED Profile

EAN: 8717748606808





The Showtec ACT Profile 150 RGBAL is a compact 150-watt RGBAL LED profile with high CRI and silent operation, suitable for theatrical applications, schools, museums, and exhibitions. It projects a bright, hard-edged beam of light within a 23° - 46° manually adjustable zoom range. The ACT Profile 150 RGBAL can be controlled via DMX, RDM, and it is equipped with one knob for manual colour and dimmer control. It comes with 5 design gobos and a four-blade shutter system, allowing you to add the proper intensity of light where it's needed.

Special features:

- 150 W RGBAL LED with high CRI for accurate colour rendering
- Suitable for theatrical applications, museums, and exhibitions
- Manually adjustable zoom, and shutters
- Hard-edged field of light
- Filter frame included

Specifications:

Source

Light Source Type	LED
Light Source Quantity	1
Light Source Power	150 W
LED Colour Type	RGBAL
Refresh Rate (Max.)	1 kHz
Illuminance @ 3 m	3260 lx
Luminous Flux (Total)	3571 lm
CRI	91
Minimum CCT	2700 K
Maximum CCT	10000 K

Optical

Beam Angle Minimum (Circular)	23°
Beam Angle Maximum (Circular)	46°
Zoom Type	Manual
Zoom Ratio	1:2
Zoom Minimum	23°
Zoom Maximum	46°

Control and Programming

Control Mode	DMX / Manual / RDM
DMX Channels	5 / 8 / 12
Protocols	DMX / RDM
Display	OLED
Display Size	1.3"
Dimmer Resolution	16 bit

Dynamic Effects

Dimmer	0-100 %

Electrical Specifications and Connections

Power Supply	100-240 V AC 50/60 Hz
Power Consumption	180 W
Fuse	3.15 A
Power Connector In	Power Pro Blue
Power Connector Out	Power Pro Grey
DMX Connector	XLR 3P In/Out
DMX Connector In	XLR 3P
DMX Connector Out	XLR 3P

Mechanical Specifications

Length (mm)	531 mm
Width (mm)	226 mm
Height (mm)	373 mm
Weight	6.15 kg
IP Rating	IP20 (indoor use only)
Housing	Aluminium / Metal

Colour	Black

Product Properties

Cooling	Forced Convection

Rigging

Mounting Options	Bracket
Safety Attachment	Yes
Safety Eyes	1

Thermal Specifications

Maximum Ambient Temperature	40°C
Minimum Operating Temperature	0°C

Included Items

Included Cables	Power Pro Cable